

10/510055

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)

(10) International Publication Number
WO 03/088238 A1

PCT

- (51) **International Patent Classification⁷:** G11B 19/02, 19/16, 15/02

(21) **International Application Number:** PCT/US03/10018

(22) **International Filing Date:** 2 April 2003 (02.04.2003)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:**
60/370,439 5 April 2002 (05.04.2002) US

(71) **Applicant (for all designated States except US): THOMSON LICENSING S.A.** [FR/FR]; 46, Quai A. Le Gallo, F-92648 Boulogne (FR).

(72) **Inventor; and**

(75) **Inventor/Applicant (for US only): KENDALL, Scott, Allan** [US/US]; 318 McIntosh Lane, Westfield, IN 46074 (US).


(74) **Agents: TRIPOLI, Joseph, S. et al.; c/o THOMSON Licensing Inc.,** Two Independence Way, Suite #2, Princeton, NJ 08540 (US).

(81) **Designated States (*national*):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States (*regional*):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: REMOTE CONTROL SYSTEM AND METHOD FOR PERSONAL VIDEO RECORDER



(57) Abstract: A video playback apparatus receives a control signal from a remote control device having a multipurpose key and assigns alternative functions to the received signal depending on the duration of time the control signal is received. For example, the remote may have a combination skip-forward multipurpose key which when pressed for less than a predetermined period such as one second, causes the video playback apparatus to invoke its skip mode, and when pressed for more than the predetermined period causes the video playback apparatus to invoke its forward, fast forward, or super fast forward mode, depending on the duration of time the key is pressed beyond invocation of the forward mode.

WO 03/088238 A1

BEST AVAILABLE COPY

WO 03/088238 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

REMOTE CONTROL SYSTEM AND METHOD FOR PERSONAL VIDEO RECORDER

Cross-Reference to Related Applications

5

[0001] Benefit of Provisional Patent Application 60/370,439, filed April 5, 2002, is claimed.

Technical Field of Invention

10 [0002] This invention relates to the field of digital video playback apparatus such as PVRs (Personal Video Recorders), to remote control devices and associated features on video playback apparatus that are controlled by the remote control devices, and methods of controlling playback of recorded television programs.

Background Art

15 [0003] The use of remote control devices to control recording and playback of video playback apparatus such as VCRs and PVRs is very well known. Remote control devices send control signals, usually infrared (IR), which are received and processed by associated video playback apparatus. For example, a user may press the "forward" button (hereinafter "key") on the remote control device, causing a coded signal to be transmitted and received by a PVR, and processed by software in a microprocessor (uP) in the PVR, resulting in the
20 playback apparatus going into fast forward playback mode.

[0004] Prior remote control systems for digital video playback apparatus include separate keys for reverse, replay, forward, skip, and play, for example.

[0005] PVRs are sometimes combined with other functions such as cable receivers, VCRs, and satellite television, and systems for receiving Internet such as WebTV, resulting in
25 more complicated remote control units ("remote controllers"). Future PVRs may be combined with other devices and functions such as DVD burners and televisions, which would require even more complicated remote controllers.

[0006] It has been a longstanding objective in the art of video playback apparatus to reduce the complexity of remotes.

30

Disclosure of Invention

[0007] This object, and others which will become apparent from the following disclosure and drawings, is addressed by the present invention which comprises in one aspect a digital video playback apparatus which responds to the duration of a control signal from a

remote, and invokes a different function for long signals, which exceed a predetermined threshold in duration, versus short control signals, which do not exceed the predetermined threshold in duration.

[0008] Another aspect of the invention comprises a remote control device to be used with a video playback apparatus having a replay-reverse multipurpose key and a skip-forward multipurpose key.

[0009] A further aspect of the invention is a system comprising the video playback apparatus and the remote controller.

[00010] The video playback apparatus can be any which responds to remote control signals from a remote control device and processes the signals to invoke playback functions.

[00011] The preferred video playback apparatus is a PVR, which employs a memory such as a hard drive to store digital files of television programs. Such PVRs have been sold under the trademarks TiVo and ReplayTV, for example. PVR-type devices, which store digital files in any type of memory system, are very suitable. In fact, any type of digital device capable of normal video playback, skip, forward, reverse, and replay functions upon command of a remote controller can be used in the invention, as long as the device can be programmed to include the novel responses to multifunction keys provided by this invention.

[00012] The preferred remote control devices are one that has a multipurpose key labeled reverse and replay, and a multipurpose key labeled forward and skip. The reverse-replay multipurpose key is pressed for less than a predetermined duration, for example one second, to invoke a replay function to review a predetermined, preceding segment, for example the last seven seconds prior to the replay function being invoked. The reverse-replay multipurpose key is pressed for more than the predetermined duration, one second in this example, to invoke the reverse function, which causes the PVR to play backwards through the digital file from the point where the function is invoked, in a manner very familiar to users of PVRs. Prior art PVRs have reverse and replay functions, but separate keys on the remote control device were necessary for those two functions. Separate keys were also necessary in prior art remote controlled PVRs for skip, which forwards the play for a predetermined time such as 30 seconds, and forward, which fast forwards the play continuously.

[00013] A preferred embodiment of the invention uses the forward-skip multipurpose key on the remote to control the speed of the forward, either toggling between several, usually three, fast forward speeds by additional presses of that key after forward is invoked, or by the user holding down that forward-skip multipurpose key. For example, after 1 second, the

reverse speed is $-2X$, after 2 seconds, the reverse speed is $-4X$, and after 3 seconds, the reverse speed is $-8X$, up to a maximum of $-16X$ after 4 seconds.

[00014] In a preferred embodiment, the remote repeats code associated with a particular multipurpose key over and over with a wait, or time gap, of a predetermined amount, usually
5 between about 1 and 10 ms., for example about 5 ms., between repetitions of the code. The decoder in the video playback apparatus interprets a gap of, say, 20 to 40 ms, wherein code is not received, to be a release of the multipurpose key and, if the "release" is interpreted as occurring at less than the predetermined amount, 1 second in this example, then the replay function of the replay-reverse key, or the skip function of the skip-forward key, is invoked.

10 [00015] A graphical user interface (GUI) is usually generated for display by any PVR-type device. The devices of the invention preferably generate a "skip" notice or icon when a control signal from a skip-forward key press is first received, and then a forward notice or icon is generated for the GUI display if the skip-forward signal is received for more than a predetermined time such as one second. Preferably, upon detection of additional presses of
15 the skip-forward key when the playback is in a forward speed mode, the forward speed is incremented or toggled to the next higher speed. Preferred forward speeds are $2X$, $4X$, $8X$, and $16X$.

[00016] Preferably upon detection of one or more additional presses of the replay-reverse key when a reverse mode has been invoked, the reverse speed is incremented or
20 toggled to the next higher reverse speed, for example from $-2X$ to $-4X$ to $-8X$ to $-16X$, depending on the number of key presses.

[00017] In each case, the corresponding notices or icons for replay, skip, $2X$, $4X$, $8X$, $16X$, $-2X$, $-4X$, $-8X$, and $-16X$ are preferably generated for the GUI when those modes are invoked.

25 Brief Description of Drawings

[00018] FIG. 1 is a block diagram of a personal video recorder apparatus according to the invention.

[00019] FIG. 2 is a flow chart showing an embodiment of a process according to the invention.

30 Modes for Carrying Out the Invention

[00020] Referring first to FIG. 1, a personal video recorder (PVR) 19 receives a source signal 11 from, for example, a satellite receiver or a cable provider, and under control of processor 18 with tuner 12 tuned to receive the source signal 11, compresses it with MPEG-2

encoder 16, stores files in MPEG-2 format in a data storage 17 such as a hard disk memory device and, when needed for display, decompresses the stored files with MPEG-2 decompressor 14. Other compressed formats can be used, for example, MPEG-4 or DV. Other memory devices can be used such as RAM (random access memory). The PVR 19 also includes a remote command receiver 22 for receiving user commands from a remote controller 20. The remote controller 20 may have an IR or RF transmitter for transmitting code signals representing user commands. As an alternative, user commands can be generated by using input devices such as buttons (not shown) attached to the PVR 19. All of the components are linked via bus 13 and controlled by processor 18.

[00021] The PVR 19 may include other functionalities such as providing a connection to the Internet through DSL, providing WinTV functionalities, and providing functionalities as a personal computer.

[00022] A stored television program, for example one that has been recorded at a user's request using the remote controller 20 and user interfaces generated by processor 18 and other components of the PVR on display 21, is played back at user command via the remote controller 20 on the display 21. The display can be any suitable viewing device such as a standard television or video monitor.

[00023] The PVR 19 can be of any design, including the types known by their trademarks TiVO and ReplayTV, and are sometimes known as digital video recorders. PVRs and other types of digital video playback apparatus are well known alternatives to VCRs for the function of time shifting of television programs. Digital playback apparatus are advantageous in several regards, including not needing blank recording tape, using electronic program guides to assist in selection of programs to be recorded, and varying speeds and types of playback modes, including "skip" which forwards the point of playback by, typically, 30 seconds, and "review" or "replay," which causes the PVR to play back at normal speed the last several seconds, typically 7 seconds, of play from the point at which replay is invoked. Each of these functions is typically carried out in response to commands from a remote controller.

[00024] Referring now to FIG. 2, a process is shown starting at 101 with the PVR in playback mode, i. e., displaying at 102 a program at normal viewing speed, known in the art as 1X speed. Upon receipt of a "skip-forward" control signal as determined at decision block 103, which is generated by pressing the corresponding key on a remote controller 20 (FIG. 1), the processor causes the PVR to generate a freeze frame at 104, wherein the playback is

"paused" at the point where the "skip-forward" control signal is received, and a user notification is generated and displayed saying "skip" at 105.

[00025] If the duration of the "skip-forward" control signal received by the PVR does not exceed one second as determined at decision block 106, the processor 18 causes the PVR to "skip" forward 30 seconds at 107 by processing the uncompressed file so as to cause a virtual skipping of video being streamed to the display. As used herein, an on-off signal is considered one continuous signal as long as the gap (the off time) is no more than a first predetermined threshold, preferably, between about 1 millisecond and 10 milliseconds. If the gap is more than a second predetermined threshold, the signals before and after the gap are not considered a part of a continuous signal; they are considered two signals. The second predetermined threshold is equal to or larger than the first, and preferably is set at 20 milliseconds. A continuous signal is normally generated by holding down a key on the remote controller 20. Two signals are generated when a user presses a key, release the key, and presses the key again.

[00026] If the "skip-forward" control signal is received for more than 1 second as determined at 106, the stored television program file is streamed at a first forward speed, i.e., 2X, and a user notification of "2X" is displayed on the display 21 at 111. The 2X mode continues until either a play control signal at 116 is received, causing the mode to be switched by the processor 18 to normal playback speed 1X at 102, or another "skip-forward" control signal is received as determined at decision block 108, causing the forward speed to increment at 109 to the next higher forward speed, 4X in this example. For each additional skip-forward control signal received as determined at decision block 108 while the system is in any forward speed, the mode switches at 109 to the next higher forward speed increment and a notice of the new speed mode is generated.

[00027] The next higher forward speed is also invoked when the "skip-forward" control signal is detected greater than a second predetermined threshold, 2 seconds in this example as determined at decision block 108, causing the display mode to be switched to 4X and a user notification of "4X". In this exemplary embodiment, for each additional second the "skip-forward" control signal persists, the PVR switches to the next higher forward speed until the highest available speed has been reached. Although the duration for moving to the next higher speed is illustrated as a constant of one second, the duration for moving to next speed may vary. For example, the duration for moving from 2X to 4X may be 0.5 second but the duration for moving from 4X to 8X may be at 0.25 second. Thus, the duration becomes

shorter for advancing to a higher speed. The increase of the speed may be in any functional relationship with the duration. For example, after holding down the "skip-forward" key over a second, the PVR switches into fast forward mode and the forward speed is directly proportional to the duration of the "skip-forward" signal until the PVR reaches its highest possible speed.

[00028] The process where a "replay-reverse" control signal is received is very similar. Again, starting with the PVR in playback mode at 101, the display is in 1X mode at 102.

When a "replay-reverse" control signal is received as determined at decision step 124, the frame is frozen, i.e., paused at 125, and a user notification such as "release to replay" or

"replay" is generated at 126. If the "replay-reverse" control signal is received for a duration less than one second as determined at decision block 114, the video is virtually reversed for 7 seconds so that the last 7 seconds previously viewed is replayed at 115. If the "replay-

reverse" control signal is received for duration of greater than 1 second as determined at the decision block 114, the program is displayed in reverse mode at a speed of -2X at 121. If the

"replay-reverse" control signal is received for greater than 2 seconds as determined at decision block 119, or if a second "replay-reverse" control signal is received, the program is displayed in -4X speed. For each additional second, the "release-reverse" signal persists, or for each additional replay-reverse control signal received as determined at decision block 119 while the system is in -2X, -4X, -8X, -16X or any other reverse speed, the mode switches at 120 to the next speed increment and a notice of the new speed mode is generated at 120. When the highest available speed has been reached, the persistence of the "release-reverse" signal will not change the speed of the PVR.

[00029] If a play control signal is received as determined at decision block 122 while the system is in a reverse mode, playback reverts to the normal speed at 102.

[00030] The principles of the invention can be applied to other keys as well such as the play key. For example, when the play key is pressed for less than a predetermined time (for example, one second), the PVR plays a video at a normal speed 1X. When the play key is pressed for more than one second, the PVR switches into a fast-forward mode having a speed of 2X. For each additional second, the play key is pressed, the PVR switches into next higher forward speed until the highest available speed has been reached.

[00031] The principles of the invention can also be applied to other digital and analog playback apparatus such as a DVD player or a VCR, in which the above three keys or their equivalents are provided in the playback apparatus or in its remote controller.

[00032] While this invention has been described with regard to a few presently preferred embodiments, those skilled in this art will readily appreciate that many alternative modes and embodiments can be carried out without departing from the spirit and scope of this invention.

CLAIMS

1. A video playback apparatus having means to invoke either replay or reverse modes upon receipt of a replay-reverse multipurpose remote control signal, depending on the duration of the replay-reverse multipurpose remote control signal, and means to invoke either skip or forward functions upon receipt of a skip-forward multipurpose remote control signal, depending on the duration of the skip-forward multipurpose remote control signal.

2. The video playback apparatus of claim 1 wherein replay is invoked upon receipt of the replay-reverse multipurpose remote control signal for a duration of time below a first replay-reverse predetermined threshold, and a first reverse speed is invoked upon receipt of the replay-reverse remote control signal for a duration of time above the first replay-reverse predetermined threshold, and wherein the skip function is invoked upon receipt of the skip-forward control signal for a duration of time below a first skip-forward predetermined threshold and a first forward function is invoked upon receipt of the skip-forward control signal for a duration of time above the first skip-forward predetermined threshold.

3. The video playback apparatus of claim 2 wherein the first skip-forward predetermined threshold is one second and the first replay-reverse predetermined threshold is one second.

4. The video playback apparatus of claim 3 having at least two reverse speeds, wherein upon receipt of the replay-reverse control signal for a duration of time greater than the first replay-reverse predetermined threshold, the first reverse speed is invoked, and upon receipt of the replay-reverse control signal for greater than a second replay-reverse predetermined threshold, a second, higher reverse speed is invoked.

5. The video playback apparatus of claim 3 having at least two forward speeds, wherein upon receipt of the first skip-forward remote control signal for a duration of time greater than the first skip-forward predetermined threshold, the first forward speed is invoked, and upon receipt of the skip-forward control signal for greater than a second skip-forward predetermined threshold, a second, higher forward speed is invoked.

6. The video playback apparatus of claim 5 wherein upon receipt of each additional skip-forward key press control signal, the next fastest forward speed is invoked, up to the highest available forward speed.

7. The video playback apparatus of claim 5 wherein the second predetermined threshold is at least one second greater than the first predetermined threshold.

8. The video playback apparatus of claim 4 wherein upon receipt of each additional replay-reverse key press control signal, the next fastest reverse speed is invoked, up to the highest available reverse speed.

9. The video playback apparatus of claim 4 wherein the second predetermined threshold is at least one second greater than the first predetermined threshold.

10. The video playback apparatus of claim 1 having 2X, 4X, 8X, and 16X forward speeds and -2X, -4X, -8X, and -16X reverse speeds.

11. The video playback apparatus of claim 1 wherein the duration is determined is calculated based on number of repetitions of code signal received, each repetition separated by a predetermined gap.

12. The video playback apparatus of claim 11 wherein the predetermined gap is between 1 and 10 milliseconds.

13. The video playback apparatus of claim 11 wherein an end of control signal is calculated upon a gap between repetitions of receipt of a code signal of greater than 20 milliseconds.

14. The video playback apparatus of claim 1 having one or more functionalities in addition to video playback, the functionalities selected from DSL, integrated receiver-decoder, WinTV, and personal computer.

15. A remote control device for use with a video playback apparatus of claim 1 having a replay-reverse multipurpose key and a skip-forward multipurpose key.

16. The remote control device of claim 15 having means to send a control signal for the duration of time a multipurpose key is pressed.

17. The remote control device of claim 15 having means to send repetitions of a control signal, each repetition separated by a predetermined gap.

18. The remote control device of claim 17 wherein the predetermined gap is between 1 and 10 milliseconds.

19. The remote control device of claim 17 wherein the predetermined gap is about 2 milliseconds.

20. A system comprising a video playback apparatus according to claim 1 and a remote control device having a replay-reverse multipurpose key and a skip-forward multipurpose key.

21. A method of controlling the operation of a digital video playback apparatus, the method comprising the steps of:

invoking a skip function upon receipt of a remote control skip-forward signal for less than a first predetermined duration, invoking a first forward speed upon receipt of the skip-forward remote control signal for greater than the first predetermined duration, invoking a second, faster forward speed upon receipt of either the skip-forward remote control signal for greater than a second predetermined duration or upon receipt of a second skip-forward remote control signal; and

invoking a replay function upon receipt of a replay-reverse remote control signal for less than a first predetermined duration, invoking a first reverse speed upon receipt of the replay-reverse remote control signal for greater than the first predetermined duration, invoking a second, faster reverse speed upon receipt of either the replay-reverse remote control signal for greater than a second predetermined duration or upon receipt of a second replay-remote control signal.

22. A electronic playback apparatus capable of receiving an external speed control signal for controlling playback speed, the electronic playback apparatus comprising:

a receiver for receiving the external speed control signal;

a microprocessor for varying the playback speed according to duration of the external speed control signal.


23. The electronic playback apparatus of claim 22, wherein the playback speed is forward speed.

24. The electronic playback apparatus of claim 22, wherein the playback speed is reverse speed.

25. The electronic playback apparatus of claim 22, wherein the external speed control signal is a signal generated by holding down a key for a skip-forward function.

26. The electronic playback apparatus of claim 22, wherein the external speed control signal is a signal generated by holding down a key for a play function.

27. The electronic playback apparatus of claim 22, wherein the external speed control signal is a signal generated by holding down a key for a replay-reverse function.

**FIG. 1**




FIG. 2

INTERNATIONAL SEARCH REPORT

PCT/US 03/10018

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G11B19/02 G11B19/16 G11B15/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 939 601 A (ENDO HIROTAKE ET AL) 3 July 1990 (1990-07-03) the whole document	1-27
X	US 5 134 497 A (KIM DONG-YOUNG) 28 July 1992 (1992-07-28) the whole document	1-27

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

14 July 2003

Date of mailing of the international search report

22/07/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Benfield, A

INTERNATIONAL SEARCH REPORT

PCT/US 03/10018

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4939601	A	03-07-1990	JP 1027060 A	30-01-1989
			JP 2663445 B2	15-10-1997
			JP 1027061 A	30-01-1989
			JP 2663446 B2	15-10-1997
			JP 1027062 A	30-01-1989
			KR 9208982 B1	12-10-1992
US 5134497	A	28-07-1992	KR 9204564 B1	08-06-1992
			GB 2234105 A , B	23-01-1991
			JP 3054753 A	08-03-1991